




Pumpentyp *		Verteilmast [m]				Vollabstützung * [m]			Abstützdruck [to]		Abmessungen [m]	
		Reichhöhe	-weite	-tiefe	Ausfalhöhe	Vorne	Hinten	Weite	Vorne	Hinten	Länge	Höhe
M 20		19,50	16,30	11,10	3,90	3,40	2,60	4,90	10,5	7,0	8,80	3,40
M 24		23,60	19,70	14,50	4,90	5,60	2,60	6,20	14,0	9,5	8,85	3,80
M 28		27,70	23,80	17,00	6,50	5,60	2,60	6,20	16,0	10,5	9,89	3,85
S 34		34,00	30,00	21,00	7,80	6,20	5,70	7,15	19,0	15,0	10,80	3,90
M 36		35,60	31,70	23,70	8,70	6,30	6,30	6,70	18,0	18,5	11,30	3,95
S 36		35,20	31,25	24,00	8,32	6,21	5,70	7,12	19,0	15,0	11,16	3,85
M 42		41,60	37,30	31,00	8,60	7,50	7,90	8,10	21,5	22,5	11,35	4,00
S 43		42,30	38,10	27,50	8,70	7,95	8,30	8,83	24,0	23,0	11,55	3,90
M 52		52,00	48,10	38,10	10,40	10,40	10,20	10,40	34,0	35,0	14,38	3,99

* Alle Daten ohne Gewähr,
genaueste Abmessungen sind den Datenblättern der Hersteller zu entnehmen.

* im einseitigen Abstützmodus ggf. geringer.